

**This Page Is Inserted by IFW Operations
and is not a part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



REC'D 06 OCT 2000

WIPO

PCT



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

XX

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

GB 00/03464


4

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated

21 SEP 2000

THIS PAGE BLANK (USPTO)

15 SEP 1977
16)

08 SEP 1999

RECEIVED BY POST

09SEP99 E475278-1 D02888
P01/7700 0.00 - 9921204.5

The Patent Office

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

DARFEN 13

2. Patent application number

(The Patent Office will fill in this part)

9921204.5

3. Full name, address and postcode of the or of each applicant (underline all surnames)

DARFEN LTD
CARR HILL
DONCASTER
DN4 8DQ

Patents ADP number (if you know it) 06501621001

If the applicant is a corporate body, give the country/state of its incorporation

UK

4. Title of the invention

FENCING SYSTEM

5. Name of your agent (if you have one)

HILLGATE PATENT SERVICES

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

6 BERNERS ROAD
ISLINGTON
LONDON N1 0AW

Patents ADP number (if you know it)

05953112002

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

a)

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

8

Claim(s)

2

Abstract

-

Drawing(s)

1+1

10. If you are also filing any of the following, state how many against each item.

Priority documents

-

Translations of priority documents

-

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

-

Request for preliminary examination and search (Patents Form 9/77)

-

Request for substantive examination (Patents Form 10/77)

-

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

NEIL MUTTICK 8.9.99

12. Name and daytime telephone number of person to contact in the United Kingdom

NEIL MUTTICK 0171 704 999

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Fencing System

The present invention relates to a fencing system, in particular, but not exclusively, to palisade fencing.

5

In a known type of palisade fencing, vertical pales are attached to a number of horizontal rails. These in turn are attached to vertical posts, which are set in the ground. The pales are usually bolted or riveted to the horizontal rails.

10

A pale is conventionally a strip of material such as metal of generally curved cross section, and is mounted upon the horizontal rails by its concave surface, so as to present its convex surface. When using such a palisade for an enclosed boundary, these convex surfaces are usually facing outwards. A known pale has a cross section of a flattened trefoil shape. Such a pale is usually formed by cold rolling a strip of metal.

15

Holes through the thickness of the pale are formed, each hole corresponding to a hole in the horizontal rail to which the pale is to be attached. A bolt is then used to fasten the pale and the horizontal rail, the head of the bolt being upon the convex surface of the pale. Similar attachment means such as rivets or the like, may be substituted.

20

This bolt head is very apparent, and offers an enticing target for vandals. Should the bolt head be removed, by being sheared off with a cold chisel for example, the pales may be removed and access gained to the area enclosed by the palisade. Also, while a pale with a generally curved cross

25

section has good structural strength axially, it has poor strength perpendicular to the axis.

GB 2 241 721 (Murphy et al) discloses a method of joining the pales
5 to the horizontal rails without using bolts, rivets or the like. The pale,
having a cross section of a flattened trefoil shape, also features a lip along
each vertical edge. A clamping plate engages with these lips, and this is
then bolted or riveted to the horizontal rail. In this manner the fastening
means is concealed from someone on the outside of the boundary. Similarly
10 to a conventional pale, this pale is cold rolled.

Like a conventional pale, the pale disclosed in Murphy has poor
strength perpendicular to its axis. Also the lips may deform if the pale is
pulled upon, so allowing the pale to be detached from the horizontal rails.

15

The object of the present invention is to provide a system of fencing
which is both structurally strong, and conceals its means of attaching the
component parts when regarded from one side of the fencing.

20 According to the invention there is provided a fencing system
including a plurality of pales, one or more substantially horizontal rails, the
rails including a substantially flat surface against which the pales are set,
wherein the pales included a tubular cross section comprising a tubular wall
a part of which is provided with holes through which a bolt or the like may
25 pass to secure the pales.

Preferably the cross section of the pale has a shape which is elongate
in the direction of the rail

Each pale may have a substantially hollow section which includes a generally concave surface, the securement means engaging with this surface and being concealed by this surface when the pale is regarded from side of the pale opposite to the concave surface.

Preferably the concave surface of the pale and surface of the rail (or an intermediate member situated between the rail and the pale) which it faces are, at least before securement, of different shapes so that a portion of the concave surface is not directly in contact with the rail, and the securement means pull upon this portion of the concave surface of the pale such that it becomes prestressed

Preferably the securement means include a bolt passing through both the rail and the concave surface. Preferably the generally concave surface includes a flat central portion. The pale is preferably formed cold rolling or welded round tube into the desired cross section. The pale can be formed directly from strip by forming the strip into a tube and then welding it and then forming the tube into desired cross section. Alternatively the pale can be cold formed from pre-made tube. The pale may also be conveniently made by extrusion.

According to another aspect of the present invention, there is provided a pale as herein defined.

25

The pale, when viewed in cross section, has a rear wall comprising a curved surface which is arranged against the horizontal rails and attached thereto, this rear wall forming part of the hollow section. When the fence is

approached from the front, the concavity of the rear wall will shield the securement means.

Furthermore, a securement means, such as a bolt, common to both
5 the rail and the pale and which tends to pull the curved surface of the pale towards the rail, will tend to flatten the concavity and prestress the pale, making the pale more rigid against the rail and making it very difficult to gain access to the securement means through the regions where the rail and pale abut.

10

A fencing system embodying the invention will now be described, by way of example, with reference to the drawings, of which;

Figure 1 shows a sectional view of the pale and the horizontal rail at the
15 attachment point.

Referring to Figure 1, the pale 20 has a generally crescent shaped hollow cross section, including a curved front wall 22, and a curved back wall 23. Rather than cusps, the regions 25,26 where the front and back walls meet are rounded. The pale then has a concave surface (the back wall 23), and a convex surface (the front wall 22).

The back wall 23 is placed against the rail 10, so that the rounded portions 25,26 rest directly against the rail. Each pale has a hole 28
25 centrally located in the concave surface, and the rail has corresponding holes 29 along its length. To secure the pale to the rail, the two holes 28,29 are aligned and a bolt 15 introduced to them. The generally concave surface of the back wall is substantially flat at the central region where the hole

occurs. This makes it easier to form the hole 28 in the pale, and easier to introduce the bolt to the hole 28.

The hole 28 in the pale is such a size that the thread of the bolt 15 engages with it, whilst the hole 29 of the rail is somewhat larger, the bolt being constrained against the rail by its head. The hole 28 is a threaded hole and in order to provide sufficient engagement with the thread of the bolt, the corresponding female thread will have to extend to a greater extent than the thickness of the wall of the pale. This additional female thread can be provided by thickening of the wall at that point, or by providing a separate nut means to the pale at the hole. Conveniently this may be provided by a threaded pot rivet which is introduced into the hole when the pale is connected to the rail from the rail side and expands to form a threaded part on the pale side of the hole 28. Alternatively a flow drilling may be used which creates an extended threaded portion from the existing hole which could be achieved by means of a self tapping bolt means.

As the bolt is tightened, the back wall 23 is drawn by the bolt's thread towards the rail 10. The crescent shape of the pale is drawn somewhat flatter as the pale is stressed.

When the pale is attached to the rail in this prestressed state, the securing bolt 15 is covered by the overhanging portions of the pale 20 when considered facing the front convex wall of the pale. In order to remove the pale from this side of the fencing, an intruder would have to force a tool or lever between one of the rounded portions 25,26 and the rail. This is difficult, since a large force is needed to overcome the prestressing of the pale.

When conventional pales are removed, the intruder will sometimes conceal that fact by resting the removed pales loosely against the pale, or temporarily fixing the pales, with chewing gum for example. To a casual observer, the pales look undamaged, but the intruder may conveniently remove the pales to gain access to the fenced off region on subsequent occasions.

The pale illustrated in figure 1 includes indentations 31,32 which run the length of the pale. When a large predetermined force is applied between pale and the rail, the pale collapses and buckles. This occurs before the bolt fails. This buckling makes it obvious from a distance that the pale has been tampered with and needs replacing. Means for testing for failed bolts or rivets have been devised such as passing along the fence with a stick rapping against the pales and detecting the change in the sound which would indicate a faulty bolt or rivet. Such labour intensive testing methods are no longer required with the fencing system of this invention.

The particular shape of the cross section of the pale and in particular the indentations 32 are important in determining the mode of failure of the pale which determines nature of the collapse and makes it possible for the pale to be observed as having failed.

The hollow section of the pale provides great strength and rigidity perpendicular to the pale's axis, whilst losing none of the axial strength.

The horizontal rails may then be attached to vertical posts embedded in the ground in the conventional manner.

The pale is formed by forming a strip first into a round tubular cross section and welding it and subsequently forming the welded tube into the desired cross section if required, though other methods could be employed. For
5 example, the pale may be is formed by rolling a shape having a similar cross section but with an open shape instead of the hollow section, and then bent and welding the shape to form the tubular section.

The pale may also be formed by extruding metal through an aperture of the
10 required shape to produce the required cross section. Other materials, such as composite materials, could equally well be used.

At the top of the pale, the front wall could be axially subdivided and the resulting strips flared out to form an upper projection, known as a
15 topping, in a similar way to conventional pales. Alternatively, the hollow section could be left open, and a topping fitted into the open top of the pale.

The horizontal rail 10 illustrated here is a standard strip, though rails having other cross sections could be used with equal facility.

20

Equally, the rail illustrated has a uniform, flat surface facing the concave surface of the pale. The rail surface could though take a variety of shapes. It could be a convex surface with a curvature less than that of the concave surface of the pale. It could also be a convex shape corresponding
25 to the concavity of the pale, and although no prestressing will occur, the bolt will be concealed by the pale.

The concealing portion of the pale need not be smoothly curved, but may be a re-entrant shape composed of flat surfaces and sharp angles, even to the extent of being rectangular. Naturally, the pale need not abut directly against the rail, but an intermediate member could be inserted between the

5 rail and the pale.

CLAIMS

- 5 1. A fencing system including a plurality of pales, one or more substantially horizontal rails, the rails including a substantially flat surface against which the pales are set, wherein the pales included a tubular cross section comprising a tubular wall a part of which is provided with holes through which a bolt or the like may pass to secure the pales.
- 10 2. A fencing system according to claim 1, wherein the cross section of the pale has a shape which is elongate in the direction of the rail.
- 15 3. A fencing system according to either previous claim wherein the section of the pale includes a generally convex surface facing away from the rail.
- 20 4. A fencing system according to any previous claim wherein the section includes a generally concave or re-entrant surface, the fastening means engaging with this surface and being concealed by this surface when the pale is regarded from side of the pale opposite to the concave surface.
- 25 5. A fencing system according to Claim 4 wherein the concave surface of the pale and surface of the rail (or an intermediate member situated between the rail and the pale) which it faces are, at least before fastening, of different shapes so that a portion of the concave surface is not directly in contact with the rail, and the fastening means pull upon this portion of the concave surface of the pale such that it becomes prestressed.

6. A fencing system according to any of claims 4-6 wherein the generally concave surface includes a flat central portion.
- 5 7. A fencing system according to either previous claim wherein the holes are provided in a thickened part of the tubular wall part and include a female thread.
8. A method of erecting a fencing system comprising supporting a rail
10 horizontally in its intended final position, and fastening a plurality of pales according to any previous claim to said rail.
9. A fencing system substantially as herein described and illustrated.
- 15 10. A pale as defined in any previous claim.
11. A pale substantially as herein described and illustrated.
12. A method of erecting a fencing system substantially as herein
20 described and illustrated.
13. Any novel and inventive feature or combination of features specifically disclosed herein within the meaning of Article 4H of the International Convention (Paris Convention).

25




Fig. 1

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (usprty)

PCT / GB 00 / 03464

F23/77 8-9-00

Agent Hillgate Patent
Services